

# 正转型



F-5SM-8.5



F-6SM-2.5~28



F-5SM-2



F-8SMA-8.5~28

型号	失速扭矩			功率		空载转速	总长度		重量		耗气量 (空转)		空气软管尺寸	
	N.m	kgf.m	ft.lb	W	PS	min <sup>-1</sup>	mm	in	kg	lb	m <sup>3</sup> /min	ft <sup>3</sup> /min	mm	in
F-5SM-8.5	5.9	0.60	4.3	130	0.18	950	153	6 1/32	0.6	1.3	0.28	9.9	6.3	1/4
F-5SM-2	23.5	2.40	17.4	120	0.16	200	187	7 3/8	0.9	2.0	0.28	9.9	6.3	1/4
F-6SM-28	3.9	0.40	2.9	290	0.40	2,800	167	6 37/64	0.7	1.5	0.34	12.0	9.5	3/8
F-6SM-21	4.4	0.45	3.3	290	0.40	2,400	167	6 37/64	0.8	1.8	0.34	12.0	9.5	3/8
F-6SM-12	7.4	0.75	5.4	290	0.40	1,300	181	7 1/8	0.9	2.0	0.34	12.0	9.5	3/8
F-6SM-8	10.8	1.10	8.0	260	0.35	900	200	7 7/8	1.0	2.2	0.34	12.0	9.5	3/8
F-6SM-5	15.7	1.60	11.6	260	0.35	600	200	7 7/8	1.0	2.2	0.34	12.0	9.5	3/8
F-6SM-2.5	28.4	2.90	21.0	260	0.35	300	213	8 25/64	1.2	2.6	0.34	12.0	9.5	3/8
F-8SMA-28	5.9	0.60	4.3	440	0.60	2,600	171	6 47/64	1.5	3.3	0.50	17.7	9.5	3/8
F-8SMA-12	11.8	1.20	8.7	440	0.60	1,300	200	7 7/8	2.0	4.4	0.50	17.7	9.5	3/8
F-8SMA-8.5	16.7	1.70	12.3	440	0.60	900	208	8 3/16	2.2	4.8	0.50	17.7	9.5	3/8

进气螺纹尺寸: PT或NPT 1/4" (除 F-5SM-系列 1/8")

订购时请指定主轴形式

## 主轴形式

缺口型	平键型	螺纹型		
型号	型号	型号	主轴螺纹尺寸	可使用的钻夹头型号
F-5SM 系列 F-6SM 系列	F-8SMA 系列 F-8SM 系列	F-6SM-5, 8, 12, 21 F-8SMA-12, 28 F-6SE, 6SF, 6PFX F-8SMA-8.5 F-10MT	3/8-24(UNF) 1/2-20(UNF)	DCK-6.5 DCK-8 DCK-10 DCK-13

\*螺纹型可安装钻夹头

## 软管连接

