



FW-5PXD-6(60)



FW-6PLD-1



FW-6PXD-6(60)




FW-6PHD-1



FW-6PMD-1(10)

型号	螺栓尺寸		推荐的扭矩范围			最大扭矩	空载速度	方头尺寸		总长度 (不含套筒)		重量 (不带套筒)		耗气量 (负载)		空气软管尺寸	
	mm	N.m	kgf.m	ft.lb	N.m			min-1	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm
FW-5PXD-6	M5	6~11	0.6~1.1	4.4~8.1	20	12,000	6.35	1/4	160	6 19/64	0.80	1.8	0.30	10.6	6.3	1/4	
FW-5PXD-60	M5	6~11	0.6~1.1	4.4~8.1	20	12,000	6.35	1/4	160	6 19/64	0.80	1.8	0.30	10.6	6.3	1/4	
FW-6PMD-1	M6	11~22	1.1~2.2	8.1~16.2	34	12,000	6.35	1/4	160	6 19/64	0.80	1.8	0.30	10.6	6.3	1/4	
FW-6PMD-10	M6	11~22	1.1~2.2	8.1~16.2	34	8,500	6.35	1/4	146	5 3/4	0.92	2.0	0.53	18.7	9.5	3/8	
FW-6PLD-1	M6	11~22	1.1~2.2	8.1~16.2	34	10,000	6.35	1/4	182	7 11/64	0.90	2.0	0.20	7.1	9.5	3/8	
FW-6PXD-6	M6	10~18	1.0~1.8	7.4~13.3	25	10,000	6.35	1/4	168	6 5/8	1.20	2.6	0.28	9.9	9.5	3/8	
FW-6PXD-60	M6	10~18	1.0~1.8	7.4~13.3	25	10,000	6.35	1/4	168	6 5/8	1.20	2.6	0.28	9.9	9.5	3/8	
FW-6PHD-1	M8	19~40	1.9~4.1	14.0~29.5	60	9,000	6.35	1/4	154	6 1/6	1.35	3.0	0.35	12.4	9.5	3/8	

进气口螺纹尺寸: PT 或 NPT 1/4".

批头尺寸		FW-*SXD-6, 7, 8, *PXD-6, *PLD-1, *PHD-1 A: 9.5 mm B: 12 mm
		FW-*SXD-60, 70, 80, *PXD-60, *PMD-10 A: 13 mm B: 16 mm