

## 枪型/后排气型



FRD-6PH-3



FRD-6PH-7



FRD-8PX

型号		钻孔能力		失速扭矩			空载转速	主轴类型及尺寸		夹持能力		侧到中心		功率		总长度		重量		最大耗气量		空气软管尺寸	
螺纹型	锥型	mm	in	N.m	kgf.m	ft.lb	min <sup>-1</sup>	螺纹	锥形	螺纹	锥形	mm	in	W	hp	mm	in	kg	lb	m <sup>3</sup> /min	ft <sup>3</sup> /min	mm	in
• FRD-5P-1		5	3/16	2.0	0.20	1.4	3,200	3/8-24	-	6.5	-	18.0	45/64	180	0.24	155	67/64	0.6	1.3	0.40	14.1	6.35	1/4
	FRD-6PX-1T	3	1/8	0.6	0.06	0.44	21,000	-	JT#1	6.5	21.0	0.53/64	290	0.39	182	711/64	1.0	2.2	0.55	19.2	9.5	3/8	
	FRD-6PH-2	5	3/16	2.7	0.27	1.98	4,300	-	JT#1	6.5	21.0	0.53/64	340	0.46	198	751/64	0.9	2.0	0.59	20.6	9.5	3/8	
	FRD-6PH-3	6.5	1/4	4.3	0.43	3.17	2,800	-	JT#1	6.5	21.0	0.53/64	340	0.46	198	751/64	0.9	2.0	0.59	20.6	9.5	3/8	
	FRD-6PH-3(8)	8	5/16	4.3	0.43	3.17	2,800	-	JT#1	8	21.0	0.53/64	340	0.46	205	85/64	1.0	2.2	0.59	20.6	9.5	3/8	
	FRD-6PH-5	10	7/16	7.5	0.75	5.53	1,300	-	JT#2S	10	21.0	0.53/64	320	0.43	243	99/16	1.4	3.1	0.59	20.6	9.5	3/8	
	FRD-6PH-7	13	1/2	15.8	0.16	11.6	600	-	JT#6	13	22.5	0.57/64	320	0.43	258	105/32	1.5	3.3	0.59	20.6	9.5	3/8	
• FRD-8PX-1		8	5/16	5.9	0.60	4.3	2,600	3/8-24	-	8.0	-	25.0	63/64	440	0.59	187	73/8	1.5	3.3	0.76	26.8	9.5	3/8
• FRD-8PX-2		10	7/16	11.8	1.20	8.6	1,300	3/8-24	-	10.0	-	26.5	13/64	440	0.59	210	89/32	1.9	4.2	0.76	26.8	9.5	3/8
• FRD-8PX-3		13	1/2	16.7	1.70	12.3	900	1/2-20	-	13.0	-	25.5	1	440	0.59	240	929/64	2.5	5.5	0.76	26.8	9.5	3/8

进气口螺纹尺寸: PT 或 NPT 1/4"

\*标有•的可提供辅助手柄

## 附件

### 钻头头



订货号	型号	主轴类型及尺寸	夹持能力
DCK-5J	FRD-5S-2T, 2TF	J.T.#D(Taper)	5mm
DCK-6.5	FRD-5S-1, 1F, 6S-2, 2F, 5P-1, 6PX-2	3/8-24(Thread)	6.5mm
DCK-8	FRD-6S-3, 3F, 6PX-3, 8PX-1	3/8-24(Thread)	8mm
DCK-10	FRD-6S-5, 5F, 6PX-5, 8PX-2	3/8-24(Thread)	10mm
DCK-13	FRD-6S-7, 7F, 6PX-7, 8PX-3, 12Z-1, 1C	1/2-20(Thread)	13mm
DCK-16	FRD-16Z-1, 1C	5/8-16(Thread)	16mm