



FW-19Z-5



FW-250-1~2



FW-320-1



FW-420-1C~2C



FW-320-1CL
(加长轴) 内置开关型



FW-420-1L
(加长轴) 外置开关型



FW-420-1CL
内置开关

型号	螺纹尺寸		推荐的扭矩范围			最大扭矩		空载速度		度方头尺寸		总长度 (不含套筒)		重量 (不含套筒)		耗气量 (负载)		空气软管尺寸	
	mm	N.m	kgf.m	ft.lb	N.m	min-1	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in			
FW-19Z-5	18	235~450	24.0~45.9	174~333	560	5,000	19.0	3/4	322.0	12 43/64	5.20	0.60	0.6	21.2	9.5	3/8"			
• FW-19Z-5C	18	235~450	24.0~45.9	174~333	560	5,000	19.0	3/4	322.0	12 43/64	5.20	0.60	0.6	21.2	9.5	3/8"			
FW-250-1	24	380~1,040	38.8~106.1	281~720	1,200	5,000	25.4	1	302.0	11 57/64	6.00	0.70	0.7	24.7	12.7	1/2"			
FW-250-1C	24	380~1,040	38.8~106.1	281~720	1,200	5,000	25.4	1	302.0	11 57/64	6.00	0.70	0.7	24.7	12.7	1/2"			
FW-250-2	24	380~1,040	38.8~106.1	281~720	1,200	5,000	19.0	3/4	302.0	11 57/64	6.00	0.70	0.7	24.7	12.7	1/2"			
FW-250-2C	24	380~1,040	38.8~106.1	281~720	1,200	5,000	19.0	3/4	302.0	11 57/64	6.00	0.70	0.7	24.7	12.7	1/2"			
FW-320-1	30~33	600~1,800	61.2~183.6	444~1333	2,300	4,800	25.4	1	353.0	13 29/32	8.70	1.00	1.0	35.3	12.7	1/2"			
FW-320-1C	30~33	600~1,800	61.2~183.6	444~1333	2,300	4,800	25.4	1	353.0	13 29/32	8.70	1.00	1.0	35.3	12.7	1/2"			
FW-320-1L	30~33	600~1,800	61.2~183.6	444~1333	2,300	4,800	25.4	1	484.0	19 1/16	10.00	1.00	1.0	35.3	12.7	1/2"			
FW-320-1CL	30~33	600~1,800	61.2~183.6	444~1333	2,300	4,800	25.4	1	484.0	19 1/16	10.00	1.00	1.0	35.3	12.7	1/2"			
• FW-420-1	36~42	900~2,500	91.8~255.0	666~1852	2,800	4,500	25.4	1	349.0	13 3/7	10.80	1.20	1.2	42.4	19.0	3/4"			
• FW-420-1C	36~42	900~2,500	91.8~255.0	666~1852	2,800	4,500	25.4	1	349.0	13 3/7	10.80	1.20	1.2	42.4	19.0	3/4"			
• FW-420-1L	36~42	900~2,500	91.8~255.0	666~1852	2,800	4,500	25.4	1	501.0	19 3/4	12.50	1.20	1.2	42.4	19.0	3/4"			
• FW-420-1CL	36~42	900~2,500	91.8~255.0	666~1852	2,800	4,500	25.4	1	501.0	19 3/4	12.50	1.20	1.2	42.4	19.0	3/4"			
• FW-420-2	36~42	900~2,500	91.8~255.0	666~1852	2,800	4,500	31.8	1 1/4	351.0	13 81/887	10.80	1.20	1.2	42.4	19.0	3/4"			
• FW-420-2C	36~42	900~2,500	91.8~255.0	666~1852	2,800	4,500	31.8	1 1/4	351.0	13 81/887	10.80	1.20	1.2	42.4	19.0	3/4"			

*进气口螺纹尺寸: PT 1/2", 除了FW-19Z-5/-5C: 3/8"

*标记 • 为加长型。*带C的机型为内置开关型。

*FW-19Z-5 为单锤型。其他型号为双爪型。