

角向砂磨机 - 旋柄型 (不适用于CE和ANSI/NA市场)



FA-5C-5
(90°)



FA-5E-7V
(90°)



FA-3CK-1
(120°)



FA-150KG-7
(120°)



FA-150K-20
(120°)

型号	最大直径				空载转速	主轴螺纹尺寸	功率		弯头高度		总长度		重量		最大耗气量		空气软管尺寸	
	砂磨盘		钢丝刷				W	hp	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
	mm	in	mm	in														
旋柄型																		
FA-5C-5	180 x - x 22.2	7 x - x 7/8	-	-	7,000	W1/2-16(F)	670	0.8	85	3 11/32	230	9	2.1	4.6	0.58	20.5	9.5	3/8
FA-5E-7V	180 x - x 22.2	7 x - x 7/8	-	-	7,000	M8-1.25P(F)	960	1.3	70	23/4	212	8 11/32	1.9	4.2	0.95	33.5	9.5	3/8
• FA-3CK-1	100 x - x 15.9	4 x - x 7/8	-	-	11,000	3/8-24UNF(M)	340	0.4	79	3 7/64	164	6 29/64	1.1	2.2	0.40	14.1	9.5	3/8
FA-150KG-7	180 x - x 22.2	7 x - x 7/8	125 x - x 15.9	5 x - x 5/8	5,500	W1/2-16(F)	900	1.2	87	3 27/64	245	9 41/64	1.8	4.0	1.15	40.6	12.7	1/2
• FA-150K-20	150 x - x 22.2	7 x - x 7/8	125 x - x 15.9	5 x - x 5/8	8,400	W1/2-16(F)	900	1.2	80	3 5/32	210	8 17/64	1.6	4.0	1.00	35.3	12.7	1/2

进气口螺纹尺寸: PT 或 NPT 3/8" 除了 FA-3CK-1: 1/4"

FA-150KG-7配有柄刷法兰。对于砂纸, 您需要法兰才能固定砂纸托盘。

• 型号没有支持手柄。(F): 内螺纹 (M): 外螺纹