

旋柄型 (不适用于CE和ANSI/NA市场)

FA-4C-1,3



FA-40-1



FA-5E-1V, 3V, 11V



FA-6C-1



FA-7C-1



FA-7E-2V



型号	最大直径 (磨料)		空载转速 min ⁻¹	主轴螺纹尺寸 in	功率		弯头高度		总长度		重量		最大耗气量		空气软管尺寸	
	mm	in			W	hp	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
旋柄型																
FA-4C-1	100x6x15.88(15)	4x1/4x5/8	13,500	M8-P1.25(F)	550	0.74	77	3.0	210	8,27	1.8	4.0	0.55	19.4	9.5	3/8
FA-4C-3	100x6x15	-	13,500	M8-P1.25(F)	550	0.74	77	3.0	210	8,27	1.8	4.0	0.55	19.4	9.5	3/8
FA-40-1	100x6x15.88(15)	4x1/4x5/8	13,500	M8-P1.25(F)	1000	1.36	74	2.9	208	8,19	1.9	4.2	1.0	35.3	9.5	3/8
FA-5C-1	125x6x22	-	10,900	M8-P1.25(F)	790	1.06	84	3.3	226	8,90	2.3	5.14	0.80	28.3	9.5	3/8
FA-5C-4	125x6x22	-	12,000	M8-P1.25(F)	790	1.06	84	3.3	226	8,90	2.3	5.1	0.80	28.3	9.5	3/8
FA-5E-1V	125x6x22	-	10,900	M8-P1.25(F)	960	1.30	70	2.8	225	8,90	2.0	4.4	0.95	33.5	9.5	3/8
FA-5E-3V	100x6x15	-	13,500	M8-P1.25(F)	960	1.30	70	2.8	225	8,90	2.0	4.4	0.95	33.5	9.5	3/8
FA-5E-11V	180x6x22	-	7,600	M8-P1.25(F)	960	1.30	70	2.8	225	8,90	2.0	4.4	0.95	33.5	9.5	3/8
FA-6C-1	180x6x22	-	7,600	W1/2-16(F)	1180	1.58	89	3.5	252	9,90	2.9	6.3	1.15	40.6	12.7	1/2
FA-6C-7	150x6x22	-	9,100	W1/2-16(F)	1180	1.58	89	3.5	252	9,90	2.7	5.9	1.15	40.6	12.7	1/2
FA-6C-10	150x6x22.2	6x1/4x7/8	9,000	W1/2-16(F)	1180	1.58	89	3.5	252	9,90	2.7	5.9	1.15	40.6	12.7	1/2
FA-6C-12	180x6x22.2	7x1/4x7/8	7,600	W1/2-16(F)	1180	1.58	89	3.5	252	9,90	2.9	6.3	1.15	40.6	12.7	1/2
FA-7C-1	180x6x22	-	7,600	W1/2-16(F)	960	1.30	89	3.5	264	10.4	3.4	7.5	1.40	49.4	12.7	1/2
FA-7E-1V	180x6x22.2	7x1/4x7/8	7,000	W1/2-16(F)	1500	2.0	89	3.5	272	10,7	3.4	7.5	1.40	49.4	12.7	1/2
FA-7E-2V	180x6x22	-	7,600	W1/2-16(F)	1500	2.0	89	3.5	272	10,7	3.1	6.8	1.40	49.4	12.7	1/2
FA-7E-3V	180x6x22.2	7x1/4x7/8	8,400	W1/2-16(F)	1590	2.15	87	3,4	272	10,7	3.1	6.8	1.40	49.4	12.7	1/2
FA-7E-4V	180x6x22.2	7x1/4x7/8	8,400	W1/2-16(F)	1590	2.15	92	3,6	272	10,7	3.1	6.8	1.40	49.4	12.7	1/2
FA-7E-5V	180x6x22.2	7x1/4x7/8	7,600	W1/2-16(F)	960	1.30	100	3,9	272	10,7	3.1	6.8	1.40	49.4	12.7	1/2
FA-9C-1	205x8x22	-	6,600	W1/2-16(F)	1700	2,28	89	3,5	309	121/6	4.2	9.2	1.65	58.3	12.7	1/2
FA-9C-2	230x9.5x22.2	9x3/8x7/8	5,900	W1/2-16(F)	1620	2,17	95	3,7	309	121/6	4.4	9.7	1.65	58.3	12.7	1/2
FA-9C-4	230x9.5x22	-	5,900	5/8-11UNC	1620	2,17	116	4,6	309	121/6	4.8	10,6	1.65	58.3	12.7	1/2
FA-9C-6	230x9.5x22	-	5,900	W1/2-16(F)	1620	2,17	95	3,7	309	121/6	4.3	9.5	1.65	58.3	12.7	1/2

进气口螺纹尺寸: PT 或 NPT 3/8" 除了 FA-9C serie 1/2"

FA-4C-3 没有支持手柄。(F): 内螺纹