



FW-6SX-5~6



FW-8SH-2



FW-10SX-5



FW-14SX-5

型号	螺栓尺寸	推荐的扭矩范围			最大扭矩	空载速度	方头尺寸		总长度 (不含套筒)		重量 (不含套筒)		耗气量 (负载)		空气软管尺寸	
		mm	N.m	kgf.m			ft.lb	N.m	min-1	mm	in	mm	in	kg	lb	m ³ /min
FW-6SX-5	M6	11~23	1.1~2.3	8.1~17.0	30	10,000	9.5	3/8	223	8 25/32	1.10	2.4	0.30	10.6	9.5	3/8
• FW-6SX-6	M6	10~18	1.0~1.8	7.4~13.3	25	10,000	9.5	3/8	223	8 25/32	1.10	2.4	0.30	10.6	9.5	3/8
• FW-8SH-2	M10	35~67	3.6~6.8	25.8~49.4	93	8,000	12.7	1/2	306	12 3/64	1.70	3.7	0.40	14.1	9.5	3/8
• FW-10SX-5	M10	50~100	5.1~10.2	36.9~73.8	150	8,000	12.7	1/2	317	12 31/64	2.20	4.8	0.40	14.1	9.5	3/8
• FW-14SX-5	M14	100~150	10.2~15.3	73.8~110.6	190	6,500	12.7	1/2	356	14 1/64	3.00	6.6	0.50	17.7	9.5	3/8

*标记 · 为油浴型。*所有型号均为双锤型。

进气口螺纹尺寸：PT 或 NPT 1/4"